



UNIVERSAL COOPERATE LTD.

Model UCL-HT3G

Coaxial Fixed Termination

2 Watts DC-3GHz



Coaxial fixed terminations absorb RF& microwave energy and are commonly used as dummy loads of antenna and transmitter. They are also used as match ports in many multiport microwave device such as circulator and directional coupler to make these ports which are not involved in the measurement be terminated in their characteristic impedance in order to ensure an accurate measurement.

UCL-HT3G coaxial fixed termination's average power 2W, frequency range dc-3GHz and feature wide frequency band, low VSWR, excellent capacity in anti-pulse and anti-burnout.

NOMINAL IMPEDANCE: 50Ω

AVERAGE POWER: 2W average to 25°C ambient

temperature, derated linearly to 0.5W @ 125°C.

PEAK POWER: 1KW (5μs pulse width with 0.2% duty cycle)

TEMPERATURE RANGE: -55°C~+125°C


CONNECTOR TYPE: 7/16(M)

WEIGHT: 125g

PHYSICAL DIMENSIONS: Φ35×51mm

Model Number	Frequency Range(GHz)	Max VSWR
UCL-HT3G	DC-3	1.10

Outline Drawings



* Dimensions are given in mm and tolerance $\pm 2\%$.

** VSWR varies according to frequency.

Universal Cooperate Ltd.

Rep Office: 46 Langham Rd Edgware, HA8 9EL The UK

Web: www.ucl-microwave.com

Email: sales@ucl-microwave.com