



UNIVERSAL COOPERATE LTD.

Model UCL-HP80G
Coaxial Fixed Attenuator
80 Watts DC-18GHz



Model Number	Frequency Range (GHz)	Attenuation Value & Accuracy (dB)				Max VSWR
		10	20	30	40	
UCL-HP80G-4	DC-4	-0.5/+1.0	-0.5/+0.8	± 1.0	± 1.0	1.20
UCL-HP80G-8	DC-8	-0.5/+1.5	-0.5/+0.8	± 1.0	± 1.0	1.30
UCL-HP80G-12.4	DC-12.4	-0.5/+2.0	-0.5/+1.0	-1.0/+2.0	-1.0/+2.0	1.35
UCL-HP80G-18	DC-18	-0.5/+3.2	-0.5/+1.0	-1.0/+2.0	-1.0/+2.0	1.45

Coaxial fixed attenuators are used in absorbing energy of transmission line, expanding power range and controlling power level, they are also used in accurately measuring power or spectrum of RF microwave transmitters accompany with small power meter, comprehensive tester or spectrum analyzer.

UCL-HP80G serial coaxial fixed attenuators' average power 1W-10KW, frequency range DC-18GHz and feature wide frequency band, low VSWR, flatness attenuation value, excellent capacity in anti-pulse and anti-burnout.

NOMINAL IMPEDANCE: 50Ω

AVERAGE POWER: 80W average to 25°C ambient temperature, derated linearly to 8W @ 125°C.

PEAK POWER: 1KW (5μs pulse width with 8% duty cycle)

3rd ORDER INTERMODULATION(Optional):

Reflected Levels(IM3) <-100dBc with two input signals @935MHz and 960MHz with average carrier power levels of +43dBm each.

TEMPERATURE RANGE: -55°C ~+125°C


CONNECTOR TYPE: N, SMA

WEIGHT: B: 270g; C: 310g

PHYSICAL DIMENSIONS:

B: Φ38×185mm; C: Φ45×185mm

Outline Drawings



* Dimensions are given in mm and tolerance ±2%.

** VSWR varies according to frequency and attenuation value.

*** VSWR and dimensions refer to connector type N.