

2.92MM COAXIAL SWITCH DC-40GHZ SP6T

UCL-CW-6T

SPECIFICATIONS

ELECTRICAL:

PRODUCT STATUS:AVAILABLE
SWITCHTYPE:SPNTMULTIPOSITION
INPUT:1
OUTPUT:6
FREQUENCY:DC-40 GHZ
IMPEDANCE:50OHM
RFCONTACTS:BREAK BEFORE MAKE
CONNECTOR:2.9 MM
TERMINATION:NO
RFDIRECTION:BI DIRECTIONAL
ACTUATOR TYPE:NORMALLY OPEN
COIL VOLTAGE:28VDC
INDICATOR:NO
SWITCHING TIME:20MS
MECHANICAL LIFE (COLD-SWITCHING):1,000,000
OPERATING TEMPERATURE:-25 TO +65
ROHS:NO
LEAD TIME(WEEKS):8



ACTUAL PRODUCT MAY DIFFER FROM PHOTO

REVISION HISTORY		APPROVED
REV	DESCRIPTION	DATE
A	PRODUCTION RELEASE	6/10/2005
		YF



Universal Cooperate Ltd.

Web:www.ucl-microwave.com

46 Langham Rd
Edgware,
HA8 9EL The UK

TITLE

SMA F'S BAND REJECTION FILTER 300-500MHZ

SIZE

A

CAGE CODE

MODEL

UCL-CW-6T

REV

A

SCALE 1:1

DOC FAMILY CW

SHEET 1 OF 1