


**Model UCL-ST25 DC-26.5GHz 50 Watts**



Coaxial fixed terminations absorb RF & microwave energy and are commonly used as dummy loads of antenna and transmitter. They are also used as match ports in many multipoint microwave device such as circulator and directional coupler to make these ports which are not involved in the measurement be terminated in their characteristic impedance in order to ensure an accurate measurement.

UCL-ST25 coaxial fixed termination's average power 25W, frequency range dc-26.5GHz and feature wide frequency band, low VSWR, excellent capacity in anti-pulse and anti-burnout.

MECHANICAL SPECIFICATIONS	
Connectors	Brass Nickel Plated
Male Pin	Brass Gold Plated
Female Pin	Beryllium Copper Gold Plated
Housing	Aluminum, Black Anodize
Temp Range	-55° C ~ +125° C
Dimensions	Φ63×63mm
Weight	130g

**RoHS Compliant: Yes**

## ELECTRICAL SPECIFICATIONS

Model Number	Frequency Range(GHz)	Max VSWR
UCL-ST25-26.5	DC-26.5	1.15-1.30

**NOMINAL IMPEDANCE:** 50Ω

**AVERAGE POWER:** 25W average to 25°C ambient temperature, derated linearly to 2W @ 125°C.

**PEAK POWER:** 1KW (5μs pulse width with 2% duty cycle)

**CONNECTOR TYPE:** SMA

### Notes:

1. Dimensions Tolerance ±2%
2. Dimensions and specifications refer to connector type N unless otherwise specified.
3. Custom designs available.