


Model UCL-WHP100-C DC-10GHz 100 Watts



Coaxial fixed attenuators are used in absorbing energy of transmission line, expanding power range and controlling power level, they are also used in accurately measuring power or spectrum of RF microwave transmitters accompany with small power meter, comprehensive tester or spectrum analyzer.

UCL-WHP serial coaxial fixed attenuators' average power from 10W-10KW, frequency range from DC-26.5GHz and feature wide frequency band, low VSWR, flatness attenuation value, excellent capacity in anti-pulse and anti-burnout.

MECHANICAL SPECIFICATIONS	
Connectors	Brass Nickel Plated
Male Pin	Brass Gold Plated
Female Pin	Beryllium Copper Gold Plated
Housing	Aluminum, Black Anodize
Temp Range	-55° C ~ +125° C
Dimensions	A:173x79x79 mm
Weight	1.5Kg

RoHS Compliant: Yes

ELECTRICAL SPECIFICATIONS

Model Number	Frequency Range(GHz)	Attenuation Value & Accuracy (dB)						Max VSWR
		3	6	10	20	30	40	
UCL-WHP100 -C-XX-2.5	DC-2.5	±0.4	±0.4	±0.3	±0.3	±0.3	±0.3	1.15
UCL-WHP100 -C-XX-4	DC-4	±0.6	±0.6	±0.5	±0.5	±0.5	±0.5	1.20
UCL-WHP100 -C-XX-6	DC-6	±0.8	±0.8	±0.75	±0.75	±0.75	±0.75	1.30
UCL-WHP100 -C-XX-8	DC-8	/	/	±1.0	±0.75	±0.75	±0.75	1.35
UCL-WHP100 -C-XX-10	DC-10	/	/	/	±0.8	±0.8	±0.8	1.50

Note: XX refer to attenuation value in dB

NOMINAL IMPEDANCE: 50Ω

AVERAGE POWER: 100W average to 25°C ambient temperature, derated linearly to 10W @ 125°C.

PEAK POWER: 5KW (5μs pulse width with 2% duty cycle)
rd

with average carrier power levels of +43dBm each.

CONNECTOR TYPE: 7/16(DC-4), N

3 ORDER INTERMODULATION(Optional): Reflected Levels(IM3) <-100dBc with two input signals @935MHz and 960MHz

Notes:

1. Dimensions Tolerance ±2%
2. Dimensions and specifications refer to connector type N unless otherwise specified.
3. Custom designs available for other special attenuation value & accuracy.